


Overview

Product information



PM-EBM-3006-M-25010000005

Male connector with direct plug in and out. Rated current: 15A; Rated voltage: 48V DC; Withstand voltage: 500V AC; Insulation resistance $> 30M \Omega$; Protection grade meet IP67 when mated; Mechanical life ≥ 100 times; Pull out force $> 60N$; Operating temperature: $-40 \sim 105^{\circ}C$; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Product advantages

- ☒ Compact structure and high space utilization
- ☒ The male connector is provided with a protective cover to protect the terminal
- ☒ Direct plug operation, convenient and fast
- ☒ Beautiful appearance, more in line with human functional design

Product certification

RoHS

Technical data

Product drawing

3D model

□

technical parameter

Rated voltage	48V DC
insulation resistance	$\geq 30M \Omega$
Mechanical life	≥ 100 次

Marking

Series	DSB
	DM

versions

Connection method	Axial screw connection
Female/Male	Female
Dimension	16A
	6B
	10B
	16B
	24B
	48B
	2 module
Number of positions	5
	15

Environmental parameters

Degree of protection	MatchingIP66
----------------------	--------------

Accessories

Business data	
Order number	25010000005
Packing unit	
Minimum order quantity	
Products weight (without packaging)	