

Overview

Product information



Bus IO-DF750-HT-200-11-1001A(H)-30050000227

Card IO housing,push-instructure,16aisleInput and output module housing,with LED display,Gold finger connection is completely disconnected

Product advantages

- ☑Hand-plugged, easy to assemble
- ☑Internal bus through bottom 6 gold-plated terminals
- ☑Equipped 16 channels functional module ,LEDs per node
- ☑Internal 2 gold-plated blade connectors for power cascading expansion
- ☑Can be installed on DIN rail

Product certification

Technical data

Product drawing

3D model

□

Connection method (IO)

wiring

PUSH-IN wiring technology

Mechanical parameters

structure type

Compact terminal module housing with signal LED

Material

PC+PA66

installation

DIN35 rail

Side by side installation

Dovetail groove clamping

label

Laser screen printing

color

C1 gray

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Connection method(IO)

Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm²
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

Dimension

length	100mm
width	12mm (main module)
Height	66.8mm

Accessories

Business data

Order number	30050000227
Packing unit	200 SKT
Minimum order quantity	200 SKT
Products weight (without packaging)	40g