

Overview			
Product information			
	A charging socket for	<b>2A-P4-03-0.0M-2207000032</b> r a charging post, cable-free, for charging electric alternating current (AC) , Type 2, IEC 62196-2,32A/250V ck, DEGSON logo	
Product advantages			
<ul> <li>☑ All Degson vehicle sockets and plu</li> <li>☑ Both power and signal contacts are</li> <li>☑ passed IATF 16949:2016 certificat</li> <li>☑ It conforms to human mechanics and</li> </ul>	e silver plated ion	s are designed in a unified manne	
Product certification			
<b>△ C</b> €	CB		
Technical data			
Product drawing			
3D model			
Environmental conditions			
Ambient temperature (operation)		-30 °C ~ 50 °C	
Ambient temperature (storage / transport)		-40 °C ~ 80 °C	
Maximum altitude		5000m(Above sea level)	
IP class		IP54(coupling)	
Electrical characteristics			
Maximum charge power		8KW	
Phase		1	
Power pin quantity		3	

Rated current of high-power contacts	32
Power contact rated voltage	250
Quantity of signal contacts	2
Signal contact rated current	2
Signal contact rated voltage	30
Signal transmission type	Pulse width adjustment
lechanical properties	
Insertion/pullout cycle	10000
Insertion force	< 100N
Pull out force	< 100N
<i>l</i> arking material	
Shell color	black
Actuation component color	Silver
Cover color	black
Customization basis	Provided according to customer requirements
Shell material	Plastic
Protective cover material	Plastic
Flammability rating	VO
Contact surface material	Ag
nvironmental Product Compliance	
REACH	conform
China RoHS	conform

Accessories

Order number	2207000032
Packing unit	36
Minimum order quantity	
Products weight (without packaging)	0.474kg