

| Overview  |                           |   |  |
|---|---------------------------|---|--|
| Product information   | Product information       |   |  |
|   | Pluggable terminal b      | /-7.62-10010010237<br>locks,Rated current:18A.Rated voltage<br>:7.62mm,Color:Green,Contact surface :Tin |  |
| Product advantages  |                           |   |  |
| <ul> <li>Well-known mounting principle all</li> <li>Suitable for 600V UL occasions</li> <li>Working voltage up to 1000V, in a</li> <li>Adaptable to multiple types of soc</li> <li>Keying parts can be installed</li> </ul> | accordance with IEC stand |   |  |
| Product certification   |                           |   |  |
| c <b>FN</b> <sup>®</sup> us   |                           |   |  |
|   |                           |   |  |
| Technical data  |                           |   |  |
| Product drawing   |                           |   |  |
| 3D model  |                           |   |  |
|   |                           |   |  |
| Packaging information   |                           |   |  |
| Type of packaging   |                           | box-packed  |  |
| Connection capacity   |                           |   |  |
| Conductor cross section solid   |                           | 0.2~2.5mm <sup>2</sup>  |  |
| Conductor cross section flexible  |                           | 0.2~2.5mm²  |  |
| feeler gauge a x b / diameter   |                           | 2.8mm x2.4mm/2.5mm  |  |
| AWG   |                           | 30~12AWG  |  |
| Torque  |                           | 0.5N.m  |  |
| Strip length  |                           | 7mm   |  |

| Electrical parameters UL |      |
|--------------------------|------|
| Rated voltage (B)        | 600V |
| Rated voltage (C)        | 600V |
| Rated current (B)        | 15A  |
| Rated current (C)        | 15A  |

## Electrical parameters IEC

| Rated voltage              | 1000∨ |
|----------------------------|-------|
| Rated voltage(III/3)       | 1000V |
| Rated current              | 18A   |
| Rated voltage(III/2)       | 1000V |
| Rated voltage(II/2)        | 1000V |
| Rated surge voltage(III/3) | 8KV   |
| Rated surge voltage(III/2) | 8KV   |
| Rated surge voltage(II/2)  | 8KV   |

## Item properties

| Connection direction | 90°                           |
|----------------------|-------------------------------|
| Pin arrangement      | Single row in a straight line |
| Connection method    | Screw connection              |
| Screwdriver          | Slotted screwdriver           |
| screw thread         | МЗ                            |
| Pitch                | 7.62mm                        |
| Number of potentials | 2                             |
| Pluggable or not     | Yes                           |
| Number of rows       | 1                             |
| flaterial data       |                               |

| Environmental items       Compliant with REACH/RoHS         Contact material       Copper alloy         Contact point metal surface       tin-plated         Contact zone metal surface       PA66         Insulation Materials       PA66         Shell color       green         Insulating material group       I         Flammability rating       UL94V-0         Mechanical tests       EC61984/ UL1059         Environmental data       EC61984/ UL1059 |                                 |  |
|--|---------------------------------|--|
| Contact point metal surface       tin-plated         Contact zone metal surface       tin-plated         Insulation Materials       PA66         Shell color       green         Insulating material group       I         Flammability rating       UL94V-0         Mechanical tests       EC61984/ UL1059  | Environmental items             | Compliant with REACH/RoHS                |
| Contact zone metal surface       tin-plated         Insulation Materials       PA66         Shell color       green         Insulating material group       I         Flammability rating       UL94V-0         Mechanical tests       EC61984/ UL1059   | Contact material                | Copper alloy                             |
| Insulation Materials       PA66         Shell color       green         Insulating material group       I         Flammability rating       UL94V-0         Mechanical tests       EC61984/ UL1059   | Contact point metal surface     | tin-plated                               |
| Shell color     green       Insulating material group     I       Flammability rating     UL94V-0       Mechanical tests     IEC61984/ UL1059  | Contact zone metal surface      | tin-plated                               |
| Insulating material group     I       Flammability rating     UL94V-0       Mechanical tests     IEC61984/ UL1059  | Insulation Materials            | PA66                                     |
| Flammability rating UL94V-0   Mechanical tests   Test Specification IEC61984/ UL1059   | Shell color                     | green                                    |
| Mechanical tests Test Specification IEC61984/ UL1059   | Insulating material group       | Ι  |
| Test Specification IEC61984/ UL1059  | Flammability rating             | UL94V-0                                  |
|  | Mechanical tests                |  |
| Environmental data   | Test Specification              | IEC61984/ UL1059                         |
|  | Environmental data              |  |
| Ambient temperature (operation) -40°C~105°C (depending on derating curve)  | Ambient temperature (operation) | -40°C~105°C(depending on derating curve) |

| 001            |                             |
|----------------|-----------------------------|
| Screwdriver    | 0.6x3.5,Slotted screwdriver |
| Operating tool |                             |
| ccessories     |                             |
| Coding strip   | 2EDG-PWI                    |
| Bridge         |                             |
| Marking strip  |                             |
|                |                             |

| Business data |             |
|---------------|-------------|
| Order number  | 10010010237 |

| Packing unit                        | 400  |
|-------------------------------------|------|
| Minimum order quantity              |      |
| Products weight (without packaging) | 3.53 |