

## Overview

### Product information



## Bus IO-DF750-001-11-2001A(H)-30050000129

Card type IO shell,can be equipped with RJ45 connector,LED indicator

### Product advantages

- ☑ Dual network ports without lights RJ45 interface
- ☑ 8-bit address interface
- ☑ Internal bus through 6 gold-plated terminals at the bottom
- ☑ Equipped with 8 channels power module, each node is equipped with LED
- ☑ Two internal gold-plated blade connectors are used for power cascade expansion
- ☑ Can be installed on DIN rail

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Dimension

width	48mm
Height	69mm
length	93.5mm

### Mechanical parameters

structure type	Compact terminal module housing with signal LED
Material	PC+PA66
installation	DIN35 rail
Side by side installation	Dovetail groove clamping

label	Laser screen printing
color	C1 gray

#### Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

#### Connection method(IO)

wiring	Spring type wiring technology
Strip length	8-9mm
Power contacts	2 blade contacts
Power load	10A
Rated current	Power: 24V Bus connector: 5V
Cross section	0.2~2.5mm <sup>2</sup>
Connectable guide cross section AWG	28~12AWG
PCB thickness	1.0mm

#### Accessories

##### Accessories

IO housing	DF750-200-11-2001A(H)
------------	-----------------------

#### Business data

Order number	30050000129
Packing unit	20
Minimum order quantity	20
Products weight (without packaging)	122.5

