

| Overview  |                             |  |
|---|-----------------------------|--|
| Product information   |                             |  |
|   |                             | W20-21010000145<br>buckle,back cover ,side entry,M20 Thread hole |
| Product advantages  |                             |  |
| <ul> <li>☑ Metal or high-strength plastic mater</li> <li>☑ Various installation methods and ou</li> <li>☑ Snap-in combination structure, dust</li> <li>Product certification</li> </ul> | utlet directions to meet on | n-site wiring requirements;                                      |
| <b>T</b> - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -  |                             |  |
| Technical data  |                             |  |
| Product drawing   |                             |  |
| 3D model  |                             |  |
|   |                             |  |
| Marking   |                             |  |
| classification  |                             | Upper Housing/base   |
| Series  |                             | В  |
| Туре  |                             | Surface mount base   |
| Specification   |                             | Low structure  |
| versions  |                             |  |
| Dimension   |                             | 6B   |
| locking Category  |                             | Single lock  |
| Thread specification  |                             | 1x M20   |
| Material characteristics  |                             |  |

| Flammability rating           | V-0                      |
|-------------------------------|--------------------------|
| RoHS                          | conform                  |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base)  | spray                    |
| Color (upper housing/base)    | Grey (RAL 7037)          |
| Material (seal)               | NBR                      |
| Material (lock catch)         | Zinc plated              |
| echnical specification        |                          |
| Limiting temperatures         | -40°C~+125℃              |
| IP class                      | IP65                     |

## Accessories

| Business data                       |             |
|-------------------------------------|-------------|
| Order number                        | 21010000145 |
| Packing unit                        | 100         |
| Minimum order quantity              | 1           |
| Products weight (without packaging) | 189         |