

| Product information | | |
|---|------------------------|--|
| | | |
| | D16A-BK-1L- | MCV-21010000243 |
| | 16A Lower base, single | buckle,no back cover,With metal protective cover |
| | | |
| Product advantages | | |
| | | |
| ☑Metal or high-strength plastic mate ☑Various installation methods and of | | - |
| ☑Snap-in combination structure, du | | |
| Product certification | | |
| | | |
| echnical data | | |
| | | |
| Product drawing | | |
| 3D model | | |
| 2 | | |
| Marking | | |
| classification | | Upper Housing/base |
| | | |
| Series | | A |
| Туре | | Hole mounting base |
| Description | | With metal dust cover |
| Specification | | Low structure |
| versions | | |
| Dimension | | 16A |
| Dimension | | |
| locking Category | | Single lock |

| Flammability rating | V-0 |
|-------------------------------|--------------------------|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |
| Material (seal) | NBR |
| Material (lock catch) | Zinc plated |
| echnical specification | |
| Limiting temperatures | -40°C~+125℃ |
| IP class | IP65 |

Accessories

| Business data | |
|-------------------------------------|-------------|
| Order number | 21010000243 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 112 |