

Overview

Product information



## MGAC-T-032A-V-5.0M-22010000061

AC charging cable with vehicle charging plug and free outlet for fast charging of electric vehicles (EVs) with alternating current (AC) via national standard AC vehicle outlets, for installation at EV charging stations (EVSE)

## Product advantages

☑ All Degson's vehicle AC plugs and power supply AC plugs adopt a unified design
☑ The surface of power and signal contacts are silver-plated
☑ Certified to IATF 16949:2016 system
☑ Ergonomic handle with additional rubber grip assembly for easy handling

Product certification



chnical data	
Product drawing	
3D model	
Environmental conditions	
Ambient temperature (operation)	-30 °C ~ 50 °C
Ambient temperature (storage / transport)	-40 °C ~ 80 °C
IP class	IP54(coupling)
	IP55(coupling)
Electrical characteristics	
Maximum charge power	24KW
Rated current of high-power contacts	32
Power contact rated voltage	440

Quantity of signal contacts	2
Signal contact rated current	2
Signal contact rated voltage	30
Projetance coding	220Ω
Resistance coding	3520Ω
Signal transmission type	Pulse width adjustment

## Marking material

Shell color	black	
EV charger color	black	
Cover color	black	
Customization basis	Provided according to customer requirements	
Shell material	Plastic	
Handle material area	Plastic	
Actuating handle material	Metal	
Protective cover material	Soft plastic	
Connection material	Plastic	
Flammability rating	VO	
Contact surface material	Ag	
Environmental Product Compliance		
REACH	conform	
China RoHS	conform	
Cable		
	3*6mm <sup>2</sup> +1*0.75mm <sup>2</sup>	
Cable composition	5*6mm <sup>2</sup> +1*0.75mm <sup>2</sup>	
	GB/T 33594-2017	
Wiring standard		

	CQC1103	
Wiring level	5 class	
Cable outer diameter	21.9±0.8mm	
Wire type	Straight line	
Cable resistance	≤ 0.00798 $\Omega$ /m (Based on the power core, at an ambient temperature of 20°C)	
Outer sheath,color	black	
Outer sheath, material	PUR	
Dimension		
Vehicle connector height	101mm(Vehicle charging connector)	
Vehicle connector width	75mm(Vehicle charging connector)	
Vehicle connector depth	236.8mm(Vehicle charging connector)	
Cable length	5000±100mm	
Strip length	100±10mm	

Accessories

Business data		
Order number	2201000061	
Packing unit	5pcs/box	
Minimum order quantity	5	
Products weight (without packaging)	13.65	