

Product information		
		O5P-FF-SH8002-20030001099 Female socket,M12,Coding A,Front panel installation/M16*1.5 ,Soldering cup
Product advantages		
 Sealing optimization, protection le Meet the harsh environment Suitable for various occasions co Compatible with the international 	onnection technology	ries products
Product certification		
c SL [®] us RoHS	REACH	
echnical data		
Product drawing		
Product drawing 3D model		
3D model		
3D model		
3D model		-40°C105°C
3D model B Environmental conditions		-40°C105°C IP68
3D model 3D model Environmental conditions		
3D model B Environmental conditions Ambient temperature IP class		
3D model B Environmental conditions Ambient temperature IP class		IP68
3D model BINITION INTERNATIONS Ambient temperature IP class General parameters Rated current		IP68 4A 60V
3D model D model D mode		IP68 4A
3D model BINITION INTERNATIONS Ambient temperature IP class General parameters Rated current		IP68 4A 60V

Overvoltage level	Π
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	VO	
Contact material	CuZn	
Material contact surface	Au	
Contact carrier material	PA	
Coil material	Zinc alloy, nickel plated	
Sealing material	Silicon	
Standards and specifications		
Standards/specifications	IEC 61076-2-101	

Accessories	
Accessories	
Sealing cap	CAP-M12-MP-8003

Business data		
Order number	20030001099	
Packing unit	/	
Minimum order quantity	100	
Products weight (without packaging)	1	