

## Overview

### Product information



## DG8HS-1.2-10080000135

Feed through terminal blocks, Rated current: 32A. Rated voltage  
(III/2) : 450V, pitch: 8.2mm, Color: natural, Contact surface : Zn

### Product advantages

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Connection capacity

Conductor cross section solid	0.2~4mm <sup>2</sup>
Conductor cross section flexible	0.5~4.0mm <sup>2</sup>
AWG	20~12AWG
Torque	0.4N.m
Strip length	9mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A

Rated current (D)	10A
-------------------	-----

#### Electrical parameters IEC

Rated current	450V
	32A
Rated voltage(III/2)	450V
Rated power frequency voltage(1min)	2KV

#### Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	8.2mm
Number of potentials	12
Pluggable or not	no

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)
---------------------------------	--

Accessories	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Business data	
Order number	10080000135
Packing unit	180
Minimum order quantity	30
Products weight (without packaging)	23.61