

## Overview

## Product information

**DG15HS-1.2-10080000058**

Feed through terminal blocks, Rated current: 76A. Rated voltage  
(III/2) : 750V, pitch: 15.0mm, Color: natural, Contact surface : Zn

## Product advantages

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Connection capacity

Conductor cross section solid	2.5~16mm <sup>2</sup>
Conductor cross section flexible	2.5~16mm <sup>2</sup>
AWG	12~10AWG
Torque	1.2N.m
Strip length	10mm

## Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A

Rated current (D)	10A
-------------------	-----

#### Electrical parameters IEC

Rated current	750V
	76A
Rated voltage(III/2)	750V
Rated power frequency voltage(1min)	3KV

#### Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	15mm
Number of potentials	12
Pluggable or not	no

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)
---------------------------------	--

Accessories	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Business data	
Order number	10080000058
Packing unit	40
Minimum order quantity	30
Products weight (without packaging)	93.8