

Overview

Product information



2EDGKFM-5.08-10010002488

Pluggable terminal blocks,Rated current:20A.Rated voltage (III/2):320V,pitch:5.08mm,Color:green,Contact surface:Tin

Product advantages

- $\ensuremath{\mbox{$\sc W$}}$ Adapt to multi-type sockets, device design is highly flexible
- ☑ Keying parts can be installed
- ☑ Universal installation method, suitable for various situations

Product certification





Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	28~12AWG
Torque	0.5N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A

Rated current (D)	10A
ration out of the	, which is a second of the sec
lectrical parameters IEC	
Rated voltage	320V
Rated current	20A
Rated voltage(III/2)	320V
Rated surge voltage(III/2)	4KV
em properties	
Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	МЗ
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1
laterial data	
Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data	
Ambient temperature (operation)	-40°C~105°C(depending on derating curve)

ool		
Screwdriver	0.6x3.5, Slotted screwdriver	
Operating tool	1	
ccessories		
Coding strip	2EDG-PWI	
Dilli	DG019-5.0	
Bridge		
Marking strip	1	

Business data	
Order number	10010002488
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	4.05